

WATER BLOCK M22 - Silicone water & oil repellent for natural & MERCOLA artificial surfaces



24-081

SECT	TION 1: IDENTIFICA	TION OF THE SUBSTANCE/M	1IXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier:	WATER BLOCK M22 - Silicone wa	ater & oil repellent for natural & artificial surfaces
		24-081	
	CAS:	Distillates (petroleum), hydrotrea	ited light
	EC:	64742-47-8	
	Index:	265-149-8 649-422-00-2	
	REACH:	01-2119484819-18-XXXX	
1.2			cure and uses advised against:
1.2	Relevant uses: Surfac		ure and uses advised against:
			an av in castion 7.2
1.3	-	All uses not specified in this section lier of the safety data sheet:	EVOCHEM S.A.
1.5	Details of the supp	ier of the safety tata sheet.	Tzaverdella Place 133 41 PHILI , ATTICA - GREECE
			Phone.: 0030 210 5590460 , 0030 210 5590155 - Fax: 0030 210 6254737 , 0030 210 5590244
			info@evochem.gr; vmergoupis@evochem.gr;
			sales@evochem.gr www.evochem.gr
1.4	Emergency telepho	ne number: National Poisoning	
SECT	TION 2: HAZARDS II	DENTIFICATION	
2.1	Classification of the	e substance or mixture:	
	CLP Regulation (EC	C) No 1272/2008:	
		-	cordance with CLP Regulation (EC) No 1272/2008.
			nt, long-term hazard, Category 3, H412
		n hazard, Category 1, H304 ble liquids, Category 3, H226	
2.2	Label elements:		
	CLP Regulation (EC	C) No 1272/2008:	
	Danger		
	Hazard statements		
	Aquatic Chronic 3: H4 Asp. Tox. 1: H304 - N	12 - Harmful to aquatic life with k Nay be fatal if swallowed and ente	
	Flam. Liq. 3: H226 - F Precautionary stat	Flammable liquid and vapour	
		ce is needed, have product contain	ner or label at hand
	P101: If medical advi P102: Keep out of rea		
		m heat, hot surfaces, sparks, oper e gloves/protective clothing/eye p	n flames and other ignition sources. No smoking
	P301+P310: IF SWAL	LOWED: Immediately call a POISO	DN CENTER/doctor
		of fire: Use ABC powder extinguish a well-ventilated place. Keep cool	
			eparated collection system used in your municipality
	Substances that co	ontribute to the classification	
	Distillates (petroleum), hydrotreated light (CAS: 64742-	47-8); Ethylbenzene (CAS: 100-41-4)
2.3	Other hazards:		
	Product fails to meet	PBT/vPvB criteria	

** Changes with regards to the previous version



WATER BLOCK M22 - Silicone water & oil repellent for natural & MERCOL artificial surfaces 24-081



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Chemical description: Mixture composed of polymers and resins in solvent

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 64742-47-8 EC: 265-149-8 Index: 649-422-00-2 REACH 01-2119484819-18-XXX	Distillates (petroleum), hydrotreated light(1) ATI Regulation 1272/2008 Asp. Tox. 1: H304 - Danger	P CLP00	75 - <100 %
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH 01-2119485493-29-XXX	N-butyl acetate(2) AT Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	P CLP00	2,4 - <4,9 %
CAS: 95-63-6 EC: 202-436-9 Index: 601-043-00-3 REACH 01-2119472135-42-XXX	1,2,4-trimethylbenzene(2) ATI Regulation 1272/2008 Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	P CLP00	2,4 - <4,9 %
CAS: 108-67-8 EC: 203-604-4 Index: 601-025-00-5 REACH 01-2120738996-34-XXX	Mesitylene(2) ATI Regulation 1272/2008 Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning	P CLP00	2,4 - <4,9 %
CAS: 1221681-75-9 EC: Non-applicable Index: Non-applicable REACH Non-applicable	Fluoropolymer ⁽²⁾ Set Regulation 1272/2008 Eye Irrit. 2: H319 - Warning	lf-classified	0,9 - <2,4 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH 01-2119489370-35-XXX	Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 -	P ATP06	0,24 - <0,9 %
CAS: 67-56-1 EC: 200-659-6 Index: 603-001-00-X REACH 01-2119433307-44-XXX	Methanol(3) ATI Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	P CLP00	<0,09 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830
⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

(3) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

3.2 Mixture:

Non-applicable

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:



WATER BLOCK M22 - Silicone water & oil repellent for natural & artificial surfaces 24-081



SECTION 4: FIRST AID MEASURES (continued)

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions



WATER BLOCK M22 - Silicone water & oil repellent for natural & artificial surfaces 24-081



SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:35 °CMaximum time:12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

	Identification		Environmental lin	nits
1,2,4-trimethylbenzene		IOELV (8h)	20 ppm	100 mg/m ³
CAS: 95-63-6		IOELV (STEL)		
EC: 202-436-9		Year	2018	
Mesitylene		IOELV (8h)	20 ppm	100 mg/m ³
CAS: 108-67-8		IOELV (STEL)		
EC: 203-604-4		Year	2018	
Ethylbenzene		IOELV (8h)	100 ppm	442 mg/m ³
CAS: 100-41-4		IOELV (STEL)	200 ppm	884 mg/m ³
EC: 202-849-4		Year	2018	
Methanol		IOELV (8h)	200 ppm	260 mg/m ³
CAS: 67-56-1		IOELV (STEL)		
EC: 200-659-6		Year	2018	•

Short exposure Long exposure Systemic Loca Systemic Loca Non-applicable N-butyl acetate Non-applicable Non-applicable Non-applicable Oral CAS: 123-86-4 Dermal Non-applicable Non-applicable Non-applicable Non-applicable EC: 204-658-1 nhalation 960 mg/m³ 960 mg/m³ 480 mg/m³ 480 mg/m³ 1,2,4-trimethylbenzene Oral Non-applicable Non-applicable Non-applicable Non-applicable CAS: 95-63-6 Dermal Non-applicable 16171 mg/kg Non-applicable Non-applicable nhalation FC: 202-436-9 100 ma/m³ 100 mg/m3 100 ma/m³ 100 ma/m³ Non-applicable Non-applicable Non-applicable Non-applicable Mesitylene Dral CAS: 108-67-8 Non-applicable Non-applicable 16171 mg/kg Non-applicable)erma EC: 203-604-4 100 ma/m^3 100 mg/m³ 100 ma/m³ 100 ma/m³ nhalation



WATER BLOCK M22 - Silicone water & oil repellent for natural & MERCOLA artificial surfaces 24-081



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Ethylbenzene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 100-41-4	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 202-849-4	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
Methanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-56-1	Dermal	40 mg/kg	Non-applicable	40 mg/kg	Non-applicable
EC: 200-659-6	Inhalation	260 mg/m ³	260 mg/m ³	260 mg/m ³	260 mg/m ³

DNEL (General population):

	Short	exposure	Long	exposure
	Systemic	Local	Systemic	Local
Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Inhalation	859,7 mg/m ³	859,7 mg/m ³	102,34 mg/m ³	102,34 mg/m ³
Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable
Inhalation	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³
Oral	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
Dermal	Non-applicable	Non-applicable	9512 mg/kg	Non-applicable
Inhalation	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³	29,4 mg/m ³
Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable
Oral	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
Dermal	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
Inhalation	50 mg/m ³	50 mg/m ³	50 mg/m ³	50 mg/m ³
		•	•	•
	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal	Systemic Oral Non-applicable Dermal Non-applicable Inhalation 859,7 mg/m³ Oral Non-applicable Inhalation 29,4 mg/m³ Oral Non-applicable Inhalation 29,4 mg/m³ Oral Non-applicable Dermal Non-applicable Dermal Non-applicable Inhalation 29,4 mg/m³ Oral Non-applicable Inhalation 29,4 mg/m³ Oral Non-applicable Inhalation 29,4 mg/m³ Oral Non-applicable Dermal Non-applicable Dermal Non-applicable Dermal Non-applicable Inhalation 8 mg/kg Dermal 8 mg/kg	OralNon-applicableNon-applicableDermalNon-applicableNon-applicableInhalation859,7 mg/m³859,7 mg/m³OralNon-applicableNon-applicableDermalNon-applicableNon-applicableDermalNon-applicableNon-applicableInhalation29,4 mg/m³29,4 mg/m³OralNon-applicableNon-applicableInhalation29,4 mg/m³29,4 mg/m³OralNon-applicableNon-applicableDermalNon-applicableNon-applicableInhalation29,4 mg/m³29,4 mg/m³OralNon-applicableNon-applicableDermalNon-applicableNon-applicableDermalNon-applicableNon-applicableOralNon-applicableNon-applicableOralNon-applicableNon-applicableDermalNon-applicableNon-applicableDermal8 mg/kgNon-applicableDermal8 mg/kgNon-applicable	SystemicLocalSystemicOralNon-applicableNon-applicableNon-applicableDermalNon-applicableNon-applicableNon-applicableInhalation859,7 mg/m³859,7 mg/m³102,34 mg/m³OralNon-applicableNon-applicable15 mg/kgDermalNon-applicableNon-applicable15 mg/kgDermalNon-applicableNon-applicable9512 mg/kgInhalation29,4 mg/m³29,4 mg/m³29,4 mg/m³OralNon-applicableNon-applicable15 mg/kgDermalNon-applicableNon-applicable9512 mg/kgInhalation29,4 mg/m³29,4 mg/m³29,4 mg/m³OralNon-applicableNon-applicable9512 mg/kgInhalation29,4 mg/m³29,4 mg/m³29,4 mg/m³OralNon-applicableNon-applicable1,6 mg/kgDermalNon-applicableNon-applicableNon-applicableInhalationNon-applicableNon-applicable15 mg/m³OralNon-applicableNon-applicable15 mg/m³OralNon-applicableNon-applicable15 mg/m³Oral8 mg/kgNon-applicable8 mg/kgDermal8 mg/kgNon-applicable8 mg/kg

PNEC:

Identification				
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg
1,2,4-trimethylbenzene	STP	2,41 mg/L	Fresh water	0,12 mg/L
CAS: 95-63-6	Soil	2,34 mg/kg	Marine water	0,12 mg/L
EC: 202-436-9	Intermittent	0,12 mg/L	Sediment (Fresh water)	13,56 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	13,56 mg/kg
Mesitylene	STP	2,02 mg/L	Fresh water	0,101 mg/L
CAS: 108-67-8	Soil	1,34 mg/kg	Marine water	0,101 mg/L
EC: 203-604-4	Intermittent	0,101 mg/L	Sediment (Fresh water)	7,86 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,86 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	20 g/kg	Sediment (Marine water)	1,37 mg/kg
Methanol	STP	100 mg/L	Fresh water	154 mg/L
CAS: 67-56-1	Soil	23,5 mg/kg	Marine water	15,4 mg/L
EC: 200-659-6	Intermittent	1540 mg/L	Sediment (Fresh water)	570,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

8.2 **Exposure controls:**

A.- General security and hygiene measures in the work place



WATER BLOCK M22 - Silicone water & oil repellent for natural & MERCOL artificial surfaces 24-081



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.
D Ocular and facial p	protection			
Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E Body protection				
Pictogram	PPE	Labelling	CEN Standard	Remarks

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing	CAT III	EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2015 EN 1149-5:2008	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN 13287:2008 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	90,59 % weight
V.O.C. density at 20 °C:	748,13 kg/m ³ (748,13 g/L)
Average carbon number:	11,45
Average molecular weight:	163,28 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

*Not relevant due to the nature of the product, not providing information property of its hazards.



WATER BLOCK M22 - Silicone water & oil repellent for natural & MERCOLA artificial surfaces 24-081



SECT	TON 9: PHYSICAL AND CHEMICAL PROPERTIES	(continued)
9.1	Information on basic physical and chemical prope	erties:
	For complete information see the product datasheet.	
	Appearance:	
	Physical state at 20 °C:	Liquid
	Appearance:	Fluid
	Colour:	Colourless
	Odour:	Characteristic
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	207 °C
	Vapour pressure at 20 °C:	241 Pa
	Vapour pressure at 50 °C:	1229 Pa (1 kPa)
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	826 kg/m³
	Relative density at 20 °C:	0,826
	Dynamic viscosity at 20 °C:	3,5 - 4,5 cP
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	<20,5 cSt
	Concentration:	810 g/L (active ingredient)
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Flammability:	
	Flash Point:	37 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	421 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Explosive:	
	Lower explosive limit:	Non-applicable *
0.2	Upper explosive limit:	Non-applicable *
9.2	Other information:	Non applicable *
	Surface tension at 20 °C:	Non-applicable *
	Refraction index: *Not relevant due to the nature of the product, not providing information of the product of t	Non-applicable *
	intervalit due to the nature of the product, not providing information	

SECTION 10: STABILITY AND REACTIVITY



WATER BLOCK M22 - Silicone water & oil repellent for natural & artificial surfaces 24-081



SECTION 10: STABILITY AND REACTIVITY (continued) 10.1 Reactivity: No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7. 10.2 Chemical stability: Chemically stable under the conditions of storage, handling and use. 10.3 Possibility of hazardous reactions: Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected. 10.4 Conditions to avoid: Applicable for handling and storage at room temperature: Shock and friction Contact with ai Increase in temperature Humidity Sunlight Not applicable Not applicable Risk of combustion Avoid direct impact Not applicable 10.5 Incompatible materials: Combustible material Combustive mate Avoid strong acids Not applicable Avoid direct impact Not applicable Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

** Changes with regards to the previous version



WATER BLOCK M22 - Silicone water & oil repellent for natural & artificial surfaces 24-081



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.

Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous as a result of a single exposure. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3

Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identificat	Identification		Acute toxicity	
1,2,4-trimethylbenzene		LD50 oral	3400 mg/kg	Rat
CAS: 95-63-6		LD50 dermal	3160 mg/kg	Rabbit
EC: 202-436-9		LC50 inhalation	11 mg/L (4 h)	Rat
N-butyl acetate		LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4		LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1		LC50 inhalation	23,4 mg/L (4 h)	Rat
Mesitylene		LD50 oral	6000 mg/kg	Rat
CAS: 108-67-8		LD50 dermal	Non-applicable	
EC: 203-604-4		LC50 inhalation	Non-applicable	
Ethylbenzene		LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4		LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4		LC50 inhalation	17,2 mg/L (4 h)	Rat
Methanol		LD50 oral	100 mg/kg	Rat
CAS: 67-56-1		LD50 dermal	300 mg/kg	Rabbit
EC: 200-659-6		LC50 inhalation	3 mg/L (4 h)	Rat


** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity: Identification Acute toxicity Species Genus 62 mg/L (96 h) Fish N-butyl acetate C50 Leuciscus idus CAS: 123-86-4 C50 73 mg/L (24 h) Daphnia magna Crustacean EC: 204-658-1 C50 Scenedesmus subspicatus 675 mg/L (72 h) Algae 1,2,4-trimethylbenzene C50 7.72 mg/L (96 h) Pimephales promelas Fish CAS: 95-63-6 C50 6.14 mg/L (48 h) Daphnia magna Crustacean EC: 202-436-9 Non-applicable C5(

** Changes with regards to the previous version





WATER BLOCK M22 - Silicone water & oil repellent for natural & MERCOLA artificial surfaces 24-081



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Persistence and degradability:				
EC: 200-659-6	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae
CAS: 67-56-1	EC50	12000 mg/L (96 h)	Nitrocra spinipes	Crustacean
Methanol	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
Ethylbenzene	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
EC: 203-604-4	EC50	53 mg/L (48 h)	Scenedesmus subspicatus	Algae
CAS: 108-67-8	EC50 50 mg/L (24 h)		Daphnia magna	Crustacean
Mesitylene	LC50	12.5 mg/L (96 h)	Carassius auratus	Fish
Identification		Acute toxicity	Species	Genus


12.2 Persistence and degradability:

Identification	D	egradability	Bioc	legradability
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	0.79	% Biodegradable	84 %
1,2,4-trimethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 95-63-6	COD	Non-applicable	Period	28 days
EC: 202-436-9	BOD5/COD	0.43	% Biodegradable	18 %
Mesitylene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 108-67-8	COD	Non-applicable	Period	14 days
EC: 203-604-4	BOD5/COD	Non-applicable	% Biodegradable	0 %
Ethylbenzene	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 100-41-4	COD	Non-applicable	Period	14 days
EC: 202-849-4	BOD5/COD	Non-applicable	% Biodegradable	90 %
Methanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-56-1	COD	1.42 g O2/g	Period	14 days
EC: 200-659-6	BOD5/COD	Non-applicable	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Identification	В	Bioaccumulation potential	
Distillates (petroleum), hydrotreated light	BCF	130	
CAS: 64742-47-8	Pow Log	3.3	
EC: 265-149-8	Potential	High	
N-butyl acetate	BCF	4	
CAS: 123-86-4	Pow Log	1.78	
EC: 204-658-1	Potential	Low	
1,2,4-trimethylbenzene	BCF	154	
CAS: 95-63-6	Pow Log	3.78	
EC: 202-436-9	Potential	High	
Mesitylene	BCF	182	
CAS: 108-67-8	Pow Log	3.42	
EC: 203-604-4	Potential	High	
Ethylbenzene	BCF	1	
CAS: 100-41-4	Pow Log	3.15	
EC: 202-849-4	Potential	Low	
Methanol	BCF	3	
CAS: 67-56-1	Pow Log	-0.77	
EC: 200-659-6	Potential	Low	

** Changes with regards to the previous version





WATER BLOCK M22 - Silicone water & oil repellent for natural & artificial surfaces 24-081



SECTION 12: ECOLOGICAL INFORMATION ** (continued) Identification Absorption/desorption Volatility Non-applicable Non-applicable N-butyl acetate (OC Henry CAS: 123-86-4 Conclusion Non-applicable)rv soil Non-applicable Surface tension FC· 204-658-1 2,478E-2 N/m (25 °C) 1oist soil Non-applicable 1,2,4-trimethylbenzene 537 624,16 Pa·m³/mol 'n lenrv CAS: 95-63-6 Low Yes Conclusion Dry soi EC: 202-436-9 2,919E-2 N/m (25 °C) Yes Surface tension loist soi 1445 Henry 888,62 Pa·m³/mol Mesitylene Koc CAS: 108-67-8 Conclusion Dry soil Low Yes EC: 203-604-4 Surface tension 2,805E-2 N/m (25 °C) Moist soil Yes Fthylbenzene 520 798,44 Pa·m³/mol Koc Henry CAS: 100-41-4 Conclusion Drv soil Moderate Yes FC· 202-849-4 2,859E-2 N/m (25 °C) Surface tension Moist soil Yes Methanol Non-applicable lenr Non-applicable CAS: 67-56-1 Non-applicable Non-applicable Drv soi onclusion FC· 200-659-6 2,355E-2 N/m (25 °C) Non-applicable Surface tension loist soil

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	It is not possible to assign a specific code, as it depends on the intended use by the user	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2017 and RID 2017:



WATER BLOCK M22 - Silicone water & oil repellent for natural & MERCOLA artificial surfaces 24-081



SECTION 14: TRANSP	ORT I	NFORMATION (continued)	
	14.1	UN number:	UN1993
	14.2	UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)
		Transport hazard class(es):	3
	_	Labels:	3
	14.4	Packing group:	Ш
3		Environmental hazards:	No
	-	Special precautions for user	
		Special regulations:	274, 601, 640E
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14 7	Transport in bulk according to	
	1 -717	Annex II of Marpol and the	
		IBC Code:	
Transport of da	ngerou	is goods by sea:	
With regard to IM	DG 38-	16:	
	14.1	UN number:	UN1993
	14.2	UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)
		Transport hazard class(es):	3
		Labels:	3
$\langle - \rangle$	14.4	Packing group:	III
		Environmental hazards:	No
3	14.6	Special precautions for user	
		Special regulations:	274, 223, 955
		EmS Codes:	F-E, S-E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Transport in bulk according to	Non-applicable
		Annex II of Marpol and the	
		IBC Code:	
Transport of da	-		
With regard to IA	TA/ICA	0 2017:	
	14.1	UN number:	UN1993
	14.2	UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (N-butyl acetate)
		Transport hazard class(es):	3
		Labels:	3
3	14.4	Packing group:	III
•		Environmental hazards:	No
~	14.6	Special precautions for user	
		Physico-Chemical properties:	see section 9
	14.7	Transport in bulk according to	Non-applicable
		Annex II of Marpol and the	
		IBC Code:	

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture: Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable Article 95, REGULATION (EU) No 528/2012: Non-applicable REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable



WATER BLOCK M22 - Silicone water & oil repellent for natural & artificial surfaces

24-081



SECTION 15: REGULATORY INFORMATION (continued)

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

New declared substances

Methanol (67-56-1) Content of the 3rd section presenting modifications (SECTION 3):

· Mesitylene (108-67-8): REACH Number

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects H304: May be fatal if swallowed and enters airways H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled Acute Tox. 4: H332 - Harmful if inhaled Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure STOT SE 1: H370 - Causes damage to organs STOT SE 3: H335 - May cause respiratory irritation STOT SE 3: H336 - May cause drowsiness or dizziness **Advice related to training:** Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their compreher and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:



WATER BLOCK M22 - Silicone water & oil repellent for natural & MERCOLA artificial surfaces 24-081



SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.