LIQUID GLASS
LIQUID GLASS COLOUR TRANSPARENT
Technical Data Sheet

Reviewed: 14.06.2026



DESCRIPTION
LIQUID GLASS COLOUR TRANSPARENT are special transparent colorants for LIQUID GLASS and other polyester and polyurethane materials.

ADVANTAGES
- Easy application
- Highly concentrated
- Super transparent
- 8 colors with mixing possibility
- Colour stability

APPLICATIONS
- LIQUID GLASS COLOUR colorants are designed for use with all our range of products: LIQUID GLASS, LIQUID GLASS CRYSTAL, LIQUID GLASS 4K ULTRA HD, LIQUID GLASS EXPRESS, LIQUID GLASS FOOD GRADE, LIQUID GLASS COLOUR BASE, LIQUID GLASS 3D FLOOR.
- LIQUID GLASS COLOUR are designed for LIQUID GLASS art projects, which can make your creations brilliant while staying crystal clear. Transparent colorants allow you to 'see through' the cast piece.
- They may be used to color an entire casting or can be used in the final or a middle layer to create a background.
- They can be blended to achieve your own custom colors.
- They are also suitable for coloring polyurethane and polyester materials.

INSTRUCTIONS FOR USE
1. Choose one or more colours to use in your construction.
2. Add a few drops to component A (resin). Always add colorant into the resin prior to mixing with component B (hardener) so that you will have plenty of time to adjust the desired shade.
3. As a general rule 2 to 3 drops of colorant per 50gr of resin will produce the desired intensity of colour.
4. Mix thoroughly with a clean stir stick, spatula or tongue depressor until the colorant is completely homogenized, with special attention to the bottom and the walls of the container.
5. Add component B (hardener) and mix well.
6. The mixture is ready to use.

REMARKS
- Too much colorant will inhibit the cure of the resin.
- If you are using LIQUID GLASS in multiple layers always mark down the amount of colorant added each time (in drops or use a precision scale) so that you can recolor the same shade in the following layers.
- By adding extra colorant, you can darken the colour. It is therefore better to start from lighter tones.
- The colour will look darker in the cup than in the casting, due to the depth of the container. Stir well to blend.
- All LIQUID GLASS COLOUR colorants can be mixed with each other. You can experiment and create your own special shades.

CLEANING
Remove as much colorant as possible from tools before cleaning. Clean all equipment immediately after use with nitro solvent.

TECHNICAL CHARACTERISTICS
Type: solvent based colorants
Consistency: liquid
Odor: characteristic of solvents
Color: 8 basic colors with unlimited mixing possibilities
Flammability: flammable
Application temperature: 10^0C - 35^0C

STORAGE
In a cool and dry place at temperatures between +5^0C - +25^0C.

SHELF LIFE
24 months in an unopened packaging, in the above mentioned storage conditions.

PACKAGING
8 colors in plastic containers 30ml

HEALTH AND SAFETY INFORMATION
Consult recent products Safety Data Sheet before use.



Yellow Orange Red Magenta Green Blue Turquoise Black

Evochem®
EVOCHEM S.A.
Tzaverdella place 13341, Fyli, Attica, Greece
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244
E-mail: info@evochem.gr Website: www.evochem.gr

ISO 9001 : 2015
UKAS MANAGEMENT SYSTEMS 0273
REACH Compliant
CLP 2016
LOW VOC

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

TECHNICAL SUPPORT
210.5590460
MONDAY TO FRIDAY 8:00 - 16:00

Evochem®
EVOCHEM S.A.
Tzaverdella place 13341, Fyli, Attica, Greece
Tel.: 210 5590460, 210 5590155 Fax: 210 5590244
E-mail: info@evochem.gr Website: www.evochem.gr