



DESCRIPTION

MINOS WHITE LITHIUM GREASE is premium grade lithium grease suitable for protection and lubrication in moving mechanical parts. It is water repellent and exhibits excellent resistance in weather conditions. It has an operating temperature range of 10°C -150°C. It finds particular use where for visual reasons a light colour grease is desirable.

ADVANTAGES

- Outstanding mechanical stability
- Prevents wear and sticking
- High viscosity
- Resistant to weather influences
- Resistant to weak acids and bases
- Corrosion prevention
- Water-humidity repellent
- Easy to use

APPLICATIONS

- Ideal for lubricating brake linkages, latches, cams, window regulators, hinges, springs, wires, cables etc.
- It can be used in anti-friction, plain bearings and pumping equipment where the ingress of water has previously reduced lubrication effectiveness.

METHOD OF APPLICATION

Surface preparation

The surface should be dry and clean, free dust, dirt and grease. Remove old varnishes, coatings and rust.

Application

Apply one layer of **MINOS WHITE LITHIUM GREASE** and allow to act for few minutes.

CLEANING

With nitro solvent or general purpose thinner

CONSUMPTION

Depends on application

TECHNICAL DATA

Form: Greasy liquid
Colour: Off white - beige
Odour: Characteristic
Density: 0,83 kg/m³
Temperature resistance: Up to 150°C
Application temperature: 10°C - 30°C

STORAGE

In a cool and dry place at temperatures between +5°C - + 35°C away from sources of ignition. Avoid direct sunlight.

SHELF LIFE

At least 5 years in unopened original package, under above mentioned storage conditions.

PACKAGING

Tube 80ml, tin 500ml

PACKAGING	CODE	BARCODE
80ml	9152	5204094091523
500ml	9153	5204094091530

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION



Acute Tox. 4: H302 - Harmful if swallowed Skin Corr. 1B: H314 - Causes severe skin burns and eye damage P101: If medical advice is needed, have product container or label at hand P102: Keep out of reach of children P264: Wash thoroughly after handling P280: Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P501: Dispose of contents and / or their container according to the separated collection system used in your municipality. Substances that contribute to the classification: Lithium hydroxide monohydrated

The directives contained in this technical data sheet are the result of our long experience from real life applications and the research testing of our research and development laboratory and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are beyond our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments. We are liable only for our products for being free from faults and of consistent quality. Users are responsible for complying with local legislation and for obtaining any required approvals or authorizations. The present edition of this technical datasheet automatically cancels any previous ones concerning the same product.

